



O-ring Mechanical Series

LY17D

- **Operational Conditions:**
 Temperature: -30℃ to +200℃
 Pressure: ≤ 0.8MPa
 Speed: ≤ 18m/s
- **Materials:**
 Stationary Ring: Q2,U2,B
 Rotary Ring: Q2,B,U2
 Secondary Seal: P,E,V
 Spring and Metal Parts: F,G
- **Applications:** Clean water,sewage water,oil and other moderately corrosive fluids.



规格/Size (公制/Metric)	D1	D2	D3	L1	L2	L3
10	21.00	17.00	19.00	15.00	7.00	4.00
12	23.00	19.00	21.00	18.00	7.00	4.00
14	25.00	21.00	23.00	22.00	7.00	4.00
16	27.00	23.00	26.00	23.00	7.00	4.00
18	33.00	27.00	29.00	24.00	10.00	5.00
20	35.00	29.00	31.00	25.00	10.00	5.00
22	37.00	31.00	33.00	25.00	10.00	5.00
24	39.00	33.00	35.00	27.00	10.00	5.00
25	40.00	34.00	36.00	27.00	10.00	5.00
28	43.00	37.00	40.00	29.00	10.00	5.00
30	45.00	39.00	43.00	30.00	10.00	5.00
32	48.00	42.00	46.00	30.00	10.00	5.00
33	48.00	42.00	46.00	39.00	10.00	5.00
35	50.00	44.00	49.00	39.00	10.00	5.00
38	56.00	49.00	53.00	42.00	13.00	6.00
40	58.00	51.00	56.00	42.00	13.00	6.00
43	61.00	54.00	59.00	47.00	13.00	6.00
45	63.00	56.00	61.00	47.00	13.00	6.00
48	66.00	59.00	64.00	47.00	13.00	6.00
50	70.00	62.00	66.00	46.00	14.00	6.00
53	73.00	65.00	69.00	56.00	14.00	6.00
55	75.00	67.00	71.00	56.00	14.00	6.00
58	78.00	70.00	76.00	56.00	14.00	6.00
60	80.00	72.00	78.00	56.00	14.00	6.00
63	83.00	75.00	81.00	56.00	14.00	6.00
65	85.00	77.00	84.00	66.00	14.00	6.00
68	90.00	81.00	88.00	64.00	16.00	7.00
70	92.00	83.00	89.00	64.00	16.00	7.00
75	97.00	88.00	98.00	64.00	16.00	7.00
80	105.00	95.00	100.00	72.00	18.00	7.00
85	110.00	100.00	107.50	72.00	18.00	7.00
90	115.00	105.00	111.00	72.00	18.00	7.00
95	120.00	110.00	119.00	72.00	18.00	7.00
100	125.00	115.00	123.80	72.00	18.00	7.00