



## O-ring Mechanical Series

### LY80

- **Operational Conditions:**  
 Temperature: -30℃ to +200℃  
 Pressure: < 1.2MPa  
 Speed: < 20m/s
- **Materials:**  
 Stationary Ring: Q2,U2,B  
 Rotary Ring: Q2,V1,U2  
 Secondary Seal: P,E,V  
 Spring and Metal Parts: F,G
- **Applications:** Clean water, sewage water, oil and other moderately corrosive fluids.



规格/Size (公制/Metric)	D1	D2	D3	L1	L2	L3
10.0	19.2	15.5	19.0	15.5	6.6	5.0
12.0	21.6	17.5	21.0	15.5	5.6	5.0
14.0	24.6	20.5	23.0	15.5	5.6	5.0
15.0	24.6	20.5	24.0	15.5	6.6	5.0
16.0	28.0	22.0	26.0	17.5	7.5	6.5
18.0	30.0	24.0	29.0	18.5	8.0	6.5
19.0	31.0	25.0	31.0	20.0	7.5	6.5
20.0	35.0	29.5	31.0	20.0	7.5	6.5
22.0	35.0	29.5	33.0	21.5	7.5	6.5
24.0	38.0	32.0	35.0	23.0	7.5	6.5
25.0	38.0	32.0	36.0	24.5	7.5	6.5
26.0	40.0	34.0	37.0	24.5	8.0	6.5
28.0	42.0	36.0	40.0	24.5	9.0	6.5
30.0	45.0	39.2	43.0	24.5	10.5	6.5
32.0	48.0	42.2	46.0	28.0	10.5	6.5
35.0	52.0	46.2	49.0	28.0	11.0	6.5
38.0	55.0	49.2	53.0	31.0	10.3	6.5
40.0	58.0	52.2	56.0	34.0	10.8	6.5
42.0	62.0	53.3	59.0	35.0	12.0	8.0
43.0	62.0	54.3	59.0	35.0	12.0	8.0
45.0	64.0	55.3	61.0	36.5	11.6	8.0
48.0	68.4	59.7	64.0	42.0	11.6	8.0
50.0	69.3	60.8	66.0	43.0	11.6	8.0
55.0	75.4	66.5	71.0	47.0	13.3	8.0
58.0	78.4	69.5	76.0	50.0	13.3	8.0
60.0	80.4	71.5	78.0	51.0	13.3	8.0
65.0	85.4	76.5	84.0	52.0	13.0	8.0
68.0	91.5	82.7	88.0	53.0	13.7	8.0
70.0	92.0	83.0	90.0	54.0	13.0	8.0
75.0	99.0	92.2	98.0	55.0	14.0	8.0
80.0	104.0	95.2	100.0	58.0	15.0	8.0