



O-ring Mechanical Series

L YM2N

- **Operational Conditions:**
 Temperature: -20°C to +180°C
 Pressure: < 1MPa
 Speed: < 15m/s
- **Materials:**
 Stationary Ring: V1,Q2,Q1,B
 Rotary Ring: B,Q1,Q2
 Secondary Seal: V,E,P
 Spring and Metal Parts: F,G
- **Seat Type:**
 Standard: LYG9
 Alternative: LYG6, LYG4
- **Applications:** Clean water, sewage water,
 Oil and other moderately corrosive fluids.



规格/Size (公制/Metric)	D3	D1	L1	L3
10	20	21	17.5	10.0
12	22	23	17.5	10.0
14	25	25	17.5	10.0
16	27	27	19.5	10.0
18	30	33	20.5	11.5
20	32	35	22.0	11.5
22	35	37	23.5	11.5
24	38	39	25.0	11.5
25	40	40	26.5	11.5
28	43	43	26.5	11.5
30	47	45	25.0	11.5
32	48	48	28.5	11.5
35	53	50	28.5	11.5
38	56	56	32.0	14.0

规格/Size (英制/inch)	D3	D1	L1	L3
0.394	0.787	0.827	0.689	0.394
0.472	0.866	0.906	0.689	0.394
0.551	0.984	0.984	0.689	0.394
0.630	1.063	1.063	0.768	0.394
0.709	1.181	1.299	0.807	0.453
0.787	1.260	1.378	0.866	0.453
0.866	1.378	1.457	0.925	0.453
0.945	1.496	1.535	0.984	0.453
0.984	1.575	1.575	1.043	0.453
1.102	1.693	1.693	1.043	0.453
1.181	1.772	1.772	0.984	0.453
1.260	1.850	1.890	1.122	0.453
1.378	1.969	1.969	1.122	0.453
1.496	2.205	2.205	1.260	0.551