



## O-ring Mechanical Series

### LY970

- Operational Conditions:**  
 Temperature: -50 °C to +200 °C  
 Pressure: ≤ 1.0MPa  
 Speed: ≤ 20m/s
- Materials:**  
 Stationary Ring: Q2, B, U2  
 Rotary Ring: U22, Q22  
 Secondary Seal: P, E, V, Aflas  
 Spring and Metal Parts: F, G
- Applications:** Clean water, sewage water,  
 Oil and other moderately corrosive fluids.



規格-Size (公制/Metric)	D1	D2	D3	D4	L	L1	L3	L4
20	33.32	29.06	34.5	37.0	44.5	35.5	15.0	4.0
25	39.85	33.84	41.0	43.0	49.0	39.0	16.0	4.0
28	43.05	37.01	42.0	46.0	51.0	41.0	16.0	4.0
30	44.63	38.61	45.5	47.5	51.0	41.0	16.0	4.0
32	46.32	40.28	47.0	49.0	54.0	44.0	16.0	4.0
35	49.48	43.46	50.0	52.5	57.0	47.0	16.0	4.0
38	52.56	46.63	53.0	55.5	57.0	47.0	16.0	4.0
40	54.25	48.13	55.0	57.0	57.0	47.0	16.0	4.0
42	55.83	49.81	55.5	58.5	57.0	47.0	16.0	4.0
45	59.02	52.98	60.0	62.0	57.0	47.0	16.0	4.0
50	65.37	59.33	66.0	68.5	68.5	58.5	18.0	5.0
55	70.03	64.01	71.0	73.0	70.0	60.0	18.0	5.0
60	76.38	70.36	77.0	81.0	73.0	63.0	18.0	5.0
65	81.23	75.21	82.0	85.5	76.0	66.0	18.0	5.0
70	85.90	79.88	87.0	90.5	78.0	66.0	18.0	5.0
75	90.77	84.73	91.5	97.0	81.0	71.0	18.0	5.0
80	100.29	94.26	99.5	103.0	87.5	77.5	18.0	5.0
85	104.77	98.93	105.5	108.0	87.5	77.5	18.0	5.0
90	109.82	103.78	110.5	114.5	92.0	82.0	18.0	5.0
95	114.30	108.46	115.5	119.0	92.0	82.0	18.0	5.0
100	119.33	113.31	120.0	124.0	92.0	82.0	18.0	5.0
105	127.00	121.16	128.0	132.0	98.5	88.5	18.0	5.0
110	131.77	126.01	133.0	137.0	85.5	88.5	18.0	5.0
115	136.52	130.68	137.5	142.00	85.5	88.5	18.0	5.0
120	142.87	137.03	144.0	147.00	105.0	95.0	18.0	5.0

規格-Size (英制/Inch)	D1	D2	D3	D4	L	L1	L3	L4
0.625	28.57	24.31	29.00	31.5	41.5	32.5	15.0	4.0
0.750	31.75	27.48	32.50	35.0	41.5	32.5	15.0	4.0
0.875	34.93	30.66	34.93	38.0	44.5	35.5	15.0	4.0
1.000	39.85	33.84	38.10	43.0	49.0	39.0	16.0	4.0
1.125	43.05	37.01	42.86	46.0	51.0	41.0	16.0	4.0
1.250	46.32	40.28	46.00	49.0	54.0	44.0	16.0	4.0
1.375	49.48	43.46	49.21	52.5	57.0	47.0	16.0	4.0
1.500	52.56	46.63	52.39	55.5	57.0	47.0	16.0	4.0
1.625	55.83	49.81	55.50	58.5	57.0	47.0	16.0	4.0
1.750	59.02	52.98	58.74	62.0	57.0	47.0	16.0	4.0
1.875	63.68	57.66	61.91	66.5	65.0	55.0	18.0	5.0
2.000	66.85	60.83	66.68	70.0	68.5	58.5	18.0	5.0
2.125	70.03	64.01	69.85	73.0	70.0	60.0	18.0	5.0
2.250	73.20	67.18	73.02	76.0	70.0	60.0	18.0	5.0
2.375	76.38	70.36	76.20	81.0	73.0	63.0	18.0	5.0
2.500	79.56	73.53	79.38	84.0	73.0	63.0	18.0	5.0
2.625	82.73	76.71	82.55	87.5	76.0	66.0	18.0	5.0
2.750	85.90	79.88	85.72	90.5	76.0	66.0	18.0	5.0
2.875	89.08	83.06	90.00	95.5	81.0	71.0	18.0	5.0
3.000	95.43	89.41	95.25	98.5	87.5	77.5	18.0	5.0
3.250	101.78	95.76	101.60	105.0	87.5	77.5	18.0	5.0
3.500	108.13	102.11	107.95	111.0	87.5	77.5	18.0	5.0
4.000	124.00	117.98	124.50	128.5	98.5	88.5	18.0	5.0