

O-ring Mechanical Series

LY58B

- **Operational Conditions:**

Temperature: -20℃ to +180℃

Pressure: ≤ 2.5MPa

Speed: ≤ 15m/s

- **Materials:**

Stationary Ring: V1,Q1,Q2,U2

Rotary Ring: B,A,U2,Q2

Secondary Seal: P,E,V,M1,M2


Spring and Metal Parts: F,G,M

- **Seat Types:**

Standard: LYBP

Alternative: LYBO

- **Applications: Clean water, sewage water,
Oil and other moderately corrosive fluids.**



规格/Size (公制/Metric)	d	d0	D3	D2	D1	L1	L2	L3	L6
14	14	18	32	21	25	30.5	12.0	18.5	6.0
16	16	20	34	23	27	30.5	12.0	18.5	6.0
18	18	22	36	27	33	31.5	13.5	20.5	6.5
20	20	24	38	29	35	31.5	13.5	20.5	6.5
22	22	26	40	31	37	31.5	13.5	20.5	6.5
24	24	28	42	33	39	34.2	13.3	20.3	6.7
25	25	30	44	34	40	34.5	13.0	20.0	7.0
28	28	33	47	37	43	37.5	12.5	19.5	7.5
30	30	35	49	39	45	38.0	12.0	19.0	8.0
32	32	38	54	42	48	38.0	12.0	19.0	8.0
33	33	38	54	42	48	38.0	12.0	19.0	8.0
35	35	40	56	44	50	38.0	12.0	19.0	8.0
38	38	43	59	49	56	39.5	13.0	20.0	10.0
40	40	45	61	51	58	39.5	13.0	20.0	10.0
43	43	48	64	54	61	39.5	13.0	20.0	10.0
45	45	50	66	56	63	39.5	13.0	20.0	10.0
48	48	53	69	59	66	39.5	13.0	20.0	10.0
50	50	55	71	62	70	44.0	13.5	20.5	11.5
53	53	58	78	65	73	44.0	13.5	20.5	11.5
55	55	60	80	67	75	44.0	13.5	20.5	11.5
58	58	63	83	70	78	49.0	13.5	20.5	11.5
60	60	65	85	72	80	49.0	13.5	20.5	11.5
63	63	68	88	75	83	49.0	13.5	20.5	11.5
65	65	70	90	77	85	49.0	13.5	20.5	11.5
70	70	75	95	83	92	55.5	14.5	21.5	13.5
75	75	80	104	88	97	55.5	14.5	21.5	13.5
80	80	85	109	95	105	55.0	15.0	22.0	13.0
85	85	90	114	100	110	60.0	15.0	22.0	13.0
90	90	95	119	105	115	60.0	15.0	22.0	13.0
95	95	100	124	110	120	60.0	15.0	22.0	13.0
100	100	105	129	115	125	60.0	15.0	22.0	13.0