



O-ring Mechanical Series

LY68

- **Operational Conditions:**
 Temperature: -40℃ to +200℃
 Pressure: < 0.8MPa
 Speed: < 18m/s
- **Materials:**
 Stationary Ring: Q2,U2,B
 Rotary Ring: U2,F
 Secondary Seal: P,E,V
 Spring and Metal Parts: F,G
- **Applications:** Clean water, sewage water, oil and other moderately corrosive fluids.



规格/Size (公制/Metric)	D1	D3	L1	L2
15.8	28.50	27.00	19.1	6.30
16.0	28.50	27.00	19.1	6.30
19.1	31.70	30.00	19.1	6.30
24.0	35.40	34.10	19.1	7.60
28.0	42.00	40.00	19.1	7.60
28.6	41.20	39.50	19.1	7.60
30.0	42.70	41.00	19.1	7.60
31.7	44.20	42.40	19.1	7.60
32.0	44.40	42.40	19.1	7.60
35.0	47.60	45.50	19.1	7.60
38.0	53.90	51.80	21.1	8.10
44.4	60.30	58.20	21.1	8.10
47.6	63.50	61.40	21.1	8.10
50.0	63.90	61.90	21.1	8.10
50.8	66.60	64.60	22.1	9.60
53.9	73.00	71.00	22.1	9.60
54.0	73.90	71.00	22.1	9.60
54.6	75.00	72.00	22.1	9.60
55.0	75.00	72.00	22.1	9.60
63.0	83.00	79.30	25.8	9.10
63.5	88.90	79.30	25.8	9.10
69.8	95.20	88.90	25.8	9.10
73.0	98.40	94.00	25.8	9.10
75.0	100.4	96.00	25.8	9.10