

O-ring Mechanical Series

LY68C

● **Operational Conditions:**

Temperature: -40°C to +200°C

Pressure: ≤ 0.8MPa

Speed: ≤ 18m/s

● **Materials:**



Stationary Ring: Q2,U2,B

Rotary Ring: U2,F

Secondary Seal: P,E,V

Spring and Metal Parts: F,G

● **Applications:** Clean water, sewage water, oil and other moderately corrosive fluids.



规格/Size (公制/Metric)	D1	D3	d1	L1	L2
16	27.00	27.0	4.00	19.10	8.60
20	35.00	31.0	5.00	19.10	10.00
22	37.00	33.0	5.00	19.10	10.00
24	39.00	34.1	5.00	19.10	10.00
25	40.00	35.2	5.00	19.10	10.00
28	43.00	40.0	5.00	19.10	10.00
30	45.00	41.0	5.00	19.10	10.00
32	48.00	42.4	5.00	19.10	10.00
33	48.00	44.0	5.00	19.10	10.00
35	50.00	45.5	5.00	19.10	10.00
38	56.00	51.8	5.00	21.10	11.00
40	58.00	53.8	5.00	21.10	11.00
43	61.00	56.0	5.00	21.10	11.00
45	63.00	58.2	5.00	21.10	11.00
48	66.00	61.4	5.00	21.10	11.00
50	70.00	61.9	5.00	21.10	13.00
55	75.00	72.0	5.00	22.10	13.00
60	80.00	76.0	5.00	25.80	13.00
63	83.00	79.3	5.00	25.80	13.00
65	85.00	82.3	5.00	25.80	13.00
70	92.00	88.9	5.00	25.80	15.30
75	97.00	96.0	5.00	25.80	15.30