



O-ring Mechanical Series

LYM74D

- **Operational Conditions:**
 Temperature: -20°C to +180°C
 Pressure: < 2.5MPa
 Speed: < 15m/s
- **Materials:**
 Stationary Ring: V1, Q1, Q2, U2, B, A
 Rotary Ring: B, A, Q1, Q2, U2
 Secondary Seal: P, E, V, M1, M2
 Spring and Metal Parts: F, G, M
- **Seat Types:**
 Standard: LYG92
 Alternative: LYG9, LYG4, LYG6
- **Applications:** Clean water, sewage water,
 Oil and other moderately corrosive fluids.



规格/Size (公制/Metric)	d	d0	D3	D2	D1	d1	L6	L1	L2	L3
14	14	18	33	21	25	3	18	53.0	10.0	17.5
16	16	20	35	23	27	3	18	53.0	10.0	17.5
18	18	22	37	27	33	3	20	53.0	11.5	19.5
20	20	24	39	29	35	3	20	53.0	11.5	19.5
22	22	26	41	31	37	3	20	53.0	11.5	19.5
24	24	28	43	33	39	3	20	54.0	11.5	19.5
25	25	30	45	34	40	3	20	54.0	11.5	19.5
28	28	33	48	37	43	3	20	54.0	11.5	19.5
30	30	35	50	39	45	3	20	54.0	11.5	19.5
32	32	38	55	42	48	3	20	56.0	11.5	19.5
33	33	38	55	42	48	3	20	56.0	11.5	19.5
35	35	40	57	44	50	3	20	57.0	11.5	19.5
38	38	43	60	49	58	4	23	57.0	14.0	22.0
40	40	45	62	51	58	4	23	57.0	14.0	22.0
43	43	48	65	54	61	4	23	57.0	14.0	22.0
45	45	50	67	56	63	4	23	56.0	14.0	22.0
48	48	53	70	59	65	4	23	56.0	14.0	22.0
50	50	55	72	62	70	4	25	63.0	15.0	23.0
53	53	58	79	65	73	4	25	67.0	15.0	23.0
55	55	60	81	67	75	4	25	67.0	15.0	23.0
58	58	63	84	70	78	4	25	74.0	15.0	23.0
60	60	65	86	72	80	4	25	74.0	15.0	23.0
63	63	68	89	75	83	4	25	79.0	15.0	23.0
65	65	70	91	77	85	4	25	88.0	15.0	23.0
70	70	75	99	83	92	4	28	76.4	18.0	26.0
75	75	80	104	88	97	4	28	76.4	18.0	26.0
80	80	85	109	95	105	4	28	76.0	18.2	26.2
85	85	90	114	100	110	4	28	76.0	18.2	26.2
90	90	95	119	105	115	4	28	76.0	18.2	26.2
95	95	100	124	110	120	4	28	76.0	17.2	25.2
100	100	105	129	115	125	4	28	76.0	17.2	25.2