

Elastomer Bellow Mechanical Seals

LY70

- **Operational Conditions:**

Temperature: -30℃ to +200℃

Pressure: ≤ 0.6MPa

Speed: ≤ 15m/s

- **Materials:**



Stationary Ring: Q2,U2,V1

Rotary Ring: Q2,B,U2

Secondary Seal: P,E,V

Spring and Metal Parts: F,G

- **Applications:** Clean water, sewage water,
Oil and other moderately corrosive fluids.



规格/Size (公制/Metric)	Model	D32	D31	D3	D2	D1	L	L2	L3
10.00	10	11.00	24.00	29.0	12.00	23.00	17.00	4.00	7.0
12.00	12S	14.20	28.55	32.0	14.00	25.00	18.20	5.00	8.0
12.00	12M	14.20	30.00	35.0	15.00	24/23	18.00	5.00	8.0
12.00	12L	14.20	33.40	38.0	14.00	25.00	18.00	5.00	6.7
16.00	16	18.20	36.45	41.5	18.00	31.00	19.80	5.00	8.0
16.00	16L	18.20	38.10	43.5	18.00	31.00	19.80	5.00	8.0
16.00	16LD	18.20	38.10	43.5	18.00	31.00	19.80	5.00	8.0
20.00	20S	21.20	38.00	43.8	21.00	35.00	20.50	5.00	9.5
20.00	20	21.20	40.00	43.8	21.00	35.00	20.50	5.00	9.5
25.00	25S	26.40	48.00	51.0	26.00	44.00	25.00	7.00	10.0
25.00	25M	26.40	47.00	51.0	26.00	44.00	25.00	7.00	12.0
25.00	25L	26.40	52.00	57.0	27.00	48.00	25.00	7.00	12.0
30.00	30	31.00	52.00	57.0	32.00	48.00	27.00	8.00	11.0
12.70	1/2"	14.20	30.00	35.0	13.50	25.40	19.20	6.20	8.0
25.80	5/8"	18.20	36.45	41.5	17.50	31.75	25.00	10.30	8.0
19.05	3/4"	21.20	40.00	43.8	20.00	34.93	25.80	10.30	9.5
25.40	1"	26.40	47.00	51.0	27.00	41.28	29.00	11.10	12.0