


Elastomer Bellow Mechanical Seals

LY502

- **Operational Conditions:**
 Temperature: -20°C to +120°C
 Pressure: < 2.5MPa
 Speed: < 15m/s
- **Materials:**
 Stationary Ring: V1,Q2,Q1,U2,U1
 Rotary Ring: B,A,Q1,Q2,U1,U2
 Secondary Seal: PE,V
 Spring and Metal Parts: F,G
- **Seat Types:**
 Standard: LYBO
 Alternative: LYBP
- **Applications:** Clean water, sewage water,
 Oil and other moderately corrosive fluids.



规格/Size (公制/Metric)	d	D3	D2	D1	L1	L2	L3
14	14	24	21	25	23.0	12.0	12.8
16	16	26	23	27	23.0	12.0	12.8
18	18	32	27	33	24.0	13.5	14.5
20	20	34	29	35	24.0	13.5	14.5
22	22	36	31	37	24.0	13.5	14.5
24	24	38	33	39	26.7	13.3	14.3
25	25	39	34	40	27.0	13.0	14.0
28	28	42	37	43	30.0	12.5	13.5
30	30	44	39	45	30.5	12.0	13.0
32	32	46	42	48	30.5	12.0	13.0
33	33	47	42	48	30.5	12.0	13.0
35	35	49	44	50	30.5	12.0	13.0
38	38	54	49	56	32.0	13.0	14.0
40	40	56	51	58	32.0	13.0	14.0
43	43	59	54	61	32.0	13.0	14.0
45	45	61	56	63	32.0	13.0	14.0
48	48	64	59	66	32.0	13.0	14.0
50	50	66	62	70	34.0	13.5	14.5
53	53	69	65	73	34.0	13.5	14.5
55	55	71	67	75	34.0	13.5	14.5
58	58	78	70	78	39.0	13.5	14.2
60	60	80	72	80	39.0	13.5	14.2
63	63	83	75	83	39.0	13.5	14.2
65	65	85	77	85	39.0	13.5	14.2
68	68	88	81	90	39.0	13.5	14.2
70	70	89	83	92	45.5	14.5	15.2
75	75	96	88	97	45.5	14.5	15.2
80	80	104	95	105	45.0	15.0	15.7
85	85	108	100	110	45.0	15.0	15.7
90	90	114	105	115	50.0	15.0	15.7
95	95	118	110	120	50.0	15.0	15.7
100	100	124	115	125	50.0	15.0	15.7