

Cartridge Mechanical Seals

LYL9

- **Operational Conditions:**

Temperature: -50℃ to +204℃

Pressure: ≤ 1.1MPa


Speed: ≤ 15m/s

- **Materials:**

Rotary Ring: B

Secondary Seal: V, E, P, K

Spring and Metal parts: F, G



规格/Size (公制/Metric)	L1	D4	D5
20.0	27.91	45.3	59.8
22.0	27.91	47.3	61.8
24.0	27.90	49.3	63.8
25.0	27.90	50.3	64.8
28.0	27.91	53.3	67.8
30.0	27.91	55.3	69.8
32.0	27.91	57.3	71.8
33.0	27.90	58.3	72.8
35.0	27.91	60.3	74.8
38.0	27.91	63.3	77.8
40.0	27.91	65.3	79.8
42.0	27.90	67.3	81.8
43.0	27.90	68.3	82.8
45.0	27.91	70.3	84.8
48.0	27.91	73.3	87.8
50.0	27.90	75.3	89.8
53.0	27.91	78.3	92.8
55.0	27.90	80.3	94.8
60.0	27.91	85.3	99.7
65.0	30.30	96.5	111.0
70.0	30.28	101.5	116.0
75.0	30.28	106.5	121.0
80.0	30.28	111.5	126.0
85.0	30.28	116.5	131.0
90.0	30.28	121.5	136.0
95.0	30.30	126.5	141.0
100.0	30.28	131.5	146.0

规格/Size Inches	L1	D4	D5
0.825"	1.098	1.622	2.192
0.750"	1.098	1.747	2.317
0.875"	1.098	1.872	2.442
1.000"	1.098	1.997	2.567
1.125"	1.098	2.122	2.692
1.250"	1.098	2.247	2.817
1.375"	1.098	2.372	2.942
1.500"	1.098	2.497	3.067
1.625"	1.098	2.622	3.192
1.750"	1.098	2.747	3.317
1.875"	1.098	2.872	3.442
2.000"	1.098	2.997	3.567
2.125"	1.098	3.122	3.692
2.250"	1.098	3.247	3.817
2.375"	1.098	3.372	3.942
2.500"	1.098	3.497	4.067
2.625"	1.192	3.866	4.436
2.750"	1.192	3.991	4.561
2.875"	1.192	4.116	4.686
3.000"	1.192	4.241	4.811
3.125"	1.192	4.366	4.936
3.250"	1.192	4.491	5.061
3.375"	1.192	4.616	5.186
3.500"	1.192	4.741	5.311
3.625"	1.192	4.866	5.436
2.750"	1.192	4.991	5.561
2.875"	1.192	5.116	5.686
4.000"	1.192	5.241	5.811