## Cartridge Mechanical Seals

## LYGU

● Operational Conditions: Temprature:30 ℃to+130 ℃ Pressure: ≤ 1.5MPa

Speed: ≤ 20m/s


■ Matetials:
Stationary Ring: Q2
Rotary Ring: B

Secondary Seal: P.E,V

Spring and Meral parts: F,G,M

Applications: Clean water,Wastewater
water,Chemical and other moderately
corrosive fluids.





規格/Size (公制/Metric)		D4 MAX			L2 MIN			
24	40.0	49.2	104.8	37.5	32.0	66.7	. 95.3	11.1
25	41.0	49.2	104.8	37.5	32.0	66.7	95.3	11.1
28	44.0	52.4	108.0	37.5	32.0	69.9	98.4	11.1
30	46.0	55.6	111.0	37.5	32.0	73.0	101.6	11.1
32	47.6	55.6	111.0	37.5	32.0	73.0	101.6	11.1
33	49.0	58.7	114.3	37.5	32.0	77.8	104.8	11.1
35	50.8	58.7	114.3	37.5	32.0	77.8	104.8	11.1
38	57.2	63.5	127.0	38.5	33.0	87.3	114.3	14.3
40	60.0	63.5	127.0	38.5	33.0	87.3	114.3	14.3
43	63.0	66.7	133.4	38.5	33.0	90.5	120.7	14.3
45	63.5	66.7	133.4	38.5	33.0	90.5	120.7	14.3
48	66.7	76.2	139.7	38.5	33.0	98.4	127.0	14.3
50	69.8	76.2	139.7	38.5	33.0	98.4	127.0	14.3
53	73.0	84.1	146.0	38.5	33.0	111.1	130.2	17.5
55	73.0	84.1	146.0	38.5	33.0	111.1	130.2	17.5
58	79.4	90.5	152.4	38.5	33.0	117.5	136.5	17.5
60	79.4	90.5	152.4	38.5	33.0	117.5	136.5	17.5
63	82.6	98.4	158.8	39.0	36.0	123.8	142.9	17.5
65	88.9	98.4	158.8	39.0	36.0	123.8	142.9	17.5
70	95.0	98.4	158.8	39.0	36.0	123.8	142.9	17.5
75	101.6	114.3	206.0	46.0	42.5	145.0	167.0	20.6
80	108.0	120.6	206.0	46.0	42.5	151.0	167.0	1 20.6
85	111.0	123.8	206.0	46.0	42.5	154.0	167.0	20.6
90.0	117.5	130.0	216.0	46.0	42.5	160.0	177.0	20.6
95	120.7	133.4	246.0	46.0	42.5	164.0	207.0	20.6
100	127.0	140.0	246.0	46.0	42.5	171.0	207.0	20.6
105	133.4	150.0	246.0	62.0	44.0	181.0	223.0	20.6
110	139.7	155.0	246.0	62.0	44.0	188.0	223.0	20.6
115	139.7	155.0	246.0	62.0	44.0	188.0	223.0	20.6
120	146.1	162.0	266.0	62.0	44.0	194.0	223.0	20.6
125	160.0	176.0	266.0	62.0	44.0	210.0	253.0	20.6
130	160.0	176.0	266.0	62.0	44.0	210.0	253.0	20.6
135	174.0	190.0	299.0	62.0	44.0	226.0	275.0	23.8
140	174.0	190.0	299.0	62.0	44.0	226.0	275.0	23.8