

Cartridge Mechanical Seals

LYGU

- **Operational Conditions:**

Temperature: 30°C to +130°C

Pressure: ≤ 1.5MPa

Speed: ≤ 20m/s

- **Materials:**



Stationary Ring: Q2

Rotary Ring: B

Secondary Seal: P,E,V

Spring and Metal parts: F,G,M

- **Applications:** Clean water, Wastewater water, Chemical and other moderately corrosive fluids.



规格/Size (英寸/Inch)	D4		D5	L1	L2 MIN	W		M
	MIN	MAX				MIN	MAX	
1.000	1.615	1.940	4.125	1.476	1.260	2.62	3.75	0.437
1.125	1.730	2.060	4.250	1.476	1.260	2.75	3.87	0.437
1.250	1.875	2.190	4.370	1.476	1.260	2.87	4.00	0.437
1.375	2.000	2.310	4.500	1.476	1.260	3.06	4.12	0.437
1.500	2.250	2.500	5.000	1.516	1.299	3.43	4.50	0.563
1.625	2.360	2.500	5.000	1.516	1.299	3.43	4.50	0.563
1.750	2.500	2.625	5.250	1.516	1.299	3.56	4.75	0.563
1.875	2.625	3.000	5.500	1.516	1.299	3.87	5.00	0.563
2.000	2.750	3.000	5.500	1.516	1.299	3.87	5.00	0.563
2.125	2.875	3.310	5.750	1.516	1.299	4.37	5.12	0.563
2.250	3.000	3.310	5.750	1.516	1.299	4.37	5.12	0.689
2.375	3.130	3.560	6.000	1.516	1.299	4.62	5.37	0.689
2.500	3.250	3.875	6.250	1.535	1.417	4.87	5.62	0.689
2.625	3.500	3.875	6.250	1.535	1.417	4.87	5.62	0.689
2.750	3.740	3.875	6.250	1.535	1.417	4.87	5.62	0.689
2.875	4.000	4.500	8.110	1.811	1.673	5.71	6.59	0.811
3.000	4.000	4.500	8.110	1.811	1.673	5.71	6.59	0.811
3.125	4.252	4.748	8.110	1.811	1.673	5.94	6.59	0.811
3.250	4.252	4.748	8.110	1.811	1.673	5.94	6.59	0.811
3.375	4.370	4.874	8.110	1.811	1.673	6.06	6.59	0.811
3.500	4.500	5.000	8.504	1.811	1.673	6.22	6.98	0.811
3.625	4.626	5.118	8.504	1.811	1.673	6.30	6.98	0.811
3.750	4.752	5.252	9.685	1.811	1.673	6.46	8.17	0.811
3.875	4.874	5.374	9.685	1.811	1.673	6.57	8.17	0.811
4.000	5.000	5.512	9.685	1.811	1.673	6.73	8.17	0.811
4.125	5.252	5.906	9.685	2.441	1.732	7.13	8.80	0.811
4.250	5.252	5.906	9.685	2.441	1.732	7.13	8.80	0.811
4.375	5.500	6.102	9.685	2.441	1.732	7.40	8.80	0.811
4.500	5.500	6.102	10.472	2.441	1.732	7.64	8.80	0.811
4.625	5.752	6.378	10.472	2.441	1.732	7.84	9.98	0.811
4.750	5.752	6.378	10.472	2.441	1.732	8.27	9.98	0.811
4.875	6.299	6.929	10.472	2.441	1.732	8.27	9.98	0.811
5.000	6.299	6.929	10.472	2.441	1.732	8.27	9.98	0.811
5.125	6.299	6.929	10.472	2.441	1.732	8.27	9.98	0.811
5.250	6.850	7.480	11.654	2.441	1.732	8.90	10.84	0.937
5.375	6.850	7.480	11.654	2.441	1.732	8.90	10.84	0.937
5.500	6.850	7.480	11.654	2.441	1.732	8.90	10.84	0.937
5.625	6.850	7.480	11.654	2.441	1.732	8.90	10.84	0.937