


## Metal Bellow Mechanical Seals

LY685

- **Operational Conditions:**  
 Temperature: -20℃ to +200℃  
 Pressure: ≤ 2.1MPa  
 Speed: ≤ 23m/s
- **Materials:**  
 Stationary Ring: U2, Q2  
 Rotary Ring: B, Q2, U2  
 Secondary Seal: V, E, P  
 Bellows: T6,  
 Spring and Metal Parts: F, G
- **Applications:** Oil, light hydrocarbon, aromatic hydrocarbon, organic solvents, weak acids, ammonia etc.



规格/Size (公制/Metric)	d	D3	D2	L3	L1
16	16	30.00	27.0	10.0	32.5
18	18	32.00	33.0	11.5	30.5
20	20	33.50	35.0	11.5	30.5
22	22	36.50	37.0	11.5	30.5
24	24	39.00	39.0	11.5	28.5
25	25	39.60	40.0	11.5	28.5
28	28	42.80	43.0	11.5	31.0
30	30	45.00	45.0	11.5	31.0
32	32	46.00	48.0	11.5	31.0
33	33	48.00	48.0	11.5	31.0
35	35	49.20	50.0	11.5	31.0
38	38	52.30	56.0	14.0	31.0
40	40	55.50	58.0	14.0	31.0
43	43	57.50	61.0	14.0	31.0
45	45	58.70	63.0	14.0	31.0
48	48	61.90	66.0	14.0	31.0
50	50	65.00	70.0	15.0	32.50
53	53	68.20	73.0	15.0	32.5
55	55	70.00	75.0	15.0	32.5
58	58	71.70	78.0	15.0	37.5
60	60	74.60	80.0	15.0	37.5
63	63	79.00	83.0	15.0	37.5
65	65	84.10	85.0	15.0	37.5
68	68	87.30	90.0	18.0	34.5
70	70	87.30	92.0	18.0	42.0
75	75	95.00	97.0	18.0	42.0
80	80	98.40	105.0	18.2	41.8
85	85	104.70	110.0	18.2	41.8
90	90	111.00	115.0	18.2	46.8
95	95	114.00	120.0	17.2	47.8
100	100	117.40	125.0	17.2	47.8