


## Metal Bellow Mechanical Seals

LY 686

- **Operational Conditions:**  
 Temperature: -20℃ to +370℃  
 Pressure: ≤ 2.0MPa  
 Speed: ≤ 23m/s
- **Materials:**  
 Stationary Ring: U2, Q2  
 Rotary Ring: B, Q2, U2  
 Secondary Seal: Graphite  
 Bellows: T6,  
 Spring and Metal parts: F, G
- **Applications:** Oil, light hydrocarbon, aromatic Hydrocarbon, organic solvents, weak acids, ammonia etc.



规格/Size (公制/Metric)	d	D3	D2	L3	L1
16	16	38.0	35.0	11.5	46.7
18	18	40.0	37.0	11.5	46.7
20	20	42.0	40.0	11.5	46.7
22	22	44.0	43.0	11.5	46.7
24	24	46.0	43.0	11.5	46.7
25	25	47.0	45.0	11.5	46.7
28	28	50.0	48.0	11.5	46.7
30	30	52.0	50.0	11.5	46.7
32	32	54.0	56.0	14.0	46.7
33	33	55.0	56.0	14.0	46.7
35	35	57.0	58.0	14.0	46.7
38	38	60.0	61.0	14.0	46.7
40	40	66.0	63.0	14.0	47.7
43	43	69.0	66.0	14.0	47.7
45	45	71.0	70.0	15.0	47.7
48	48	74.0	73.0	15.0	47.7
50	50	76.0	75.0	15.0	47.7
53	53	79.0	78.0	15.0	47.7
55	55	81.0	80.0	15.0	47.7
58	58	85.0	83.0	15.0	53.2
60	60	87.0	85.0	15.0	53.2
63	63	90.0	90.0	18.0	53.2
65	65	92.0	92.0	18.0	53.2
68	68	95.0	97.0	18.0	53.2
70	70	97.0	97.0	18.0	53.2
75	75	102.0	105.0	18.2	53.0
80	80	107.0	110.0	18.2	53.0
85	85	112.0	115.0	18.2	53.0
90	90	117.0	120.0	17.2	54.0
95	95	122.0	125.0	17.2	54.0
100	100	127.0	134.3	20.0	54.2